



## 2026 LEGIT Modified Rules

These rules are in effect as of January 1st, 2026 through December 31<sup>st</sup>, 2026

Rule changes/amendments or clarifications in red

### Option 1: Midwest Mod <https://www.powristockmod.com/downloads/get.aspx?i=1168994>

Exceptions: 4 Barrell Carburetor allowed.

-Must utilize 6200 rpm or less chip.

### Option 2: B-Mod <https://www.powristockmod.com/downloads/get.aspx?i=1168993>

Exceptions: 4 Barrell Carburetor allowed for Spec engine and 602 Crate Engine.

-602 Crate Engine must utilize 6200 rpm or less chip

-Spec engine must utilize 5800 rpm or less chip.

### Option 3: IMCA Style Modified <https://www.imca.com/wp-content/uploads/2025/11/2026-Modified-Rules.pdf>

Exceptions: Solid "Pull Bar"/Top link required.

-604 Crate Engine must utilize 5500 rpm or less chip

-Open/Spec Engine must utilize 5500 rpm or less chip

**Tires:** American Racer KK704 or Hoosier G60-15.

**SAFETY EQUIPMENT:** Rules apply at all times car is on track. Snell-rated SA2015 or SA2020 helmet required. *Fire retardant roll bar padding recommended in driver compartment.* SFI-approved full fire suit required. Fire retardant gloves, shoes and neck brace (or head and neck restraint) required. Right and left seat head supports required if using head and neck restraint system. *Recommended: Fire retardant head sock and underwear, collapsible steering shaft.* Driver-side window net required, minimum 16 inch by 20 inch ribbon or mesh style, and must be mounted to roll cage so latch is at top front of window. Maximum four inch tall visor attached to window net. Minimum two inch wide SFI-approved five point safety belt assembly required, must be mounted securely to main roll cage. *Recommended: Safety belts no more than two years old.* Kill switch required within easy reach of driver and must be clearly marked 'OFF' and 'ON'.

**EIRI:** (Except in rare instances) Decisions of LEGIT Officials are final and binding without exception.

